

DESCRIPTION:

PEAK® COOL Antifreeze + Coolant is an orange-colored, ethylene glycol based antifreeze that may be used in all General Motors vehicles requiring DEX-COOL® antifreeze + coolant, newer Ford vehicles requiring Motorcraft specialty orange engine coolant, as well as other automobiles, light duty trucks and motorcycles with aluminum radiators. It's a patened formula that features long lasting inhibitors providing long term protection against damaging rust and corrosion.

BENEFITS:

- · Compatible for use in all automobiles, light duty trucks and motorcycles
- Provides 150,000 miles or 5 years of maximum protection when a complete cooling system flush and fill is performed
- Meets European phosphate-free and Japanese silicate-free requirements

Meets ASTM D-3306 + ASTM D-4340 **Properties Typical Values** Specific Gravity 60/60°F

1.115-1.124 325°F Min.* 50 ml./3 sec. Max. 8.5 Min-9.2 Max. 250°F Min. 5% Max.

95% Min. Orange

ASTM Test Method

| |)-1122 | |
|---|--------|--|
| |)-1120 | |
| |)-1881 | |
| |)-1287 | |
| |)-92 | |
| |)-1123 | |
| Г |)-5U5 | |

| % of Cooling System Capacity | PROTEC Freezing Down to | TS FROM Boiling Up to* |
|---------------------------------|----------------------------|---------------------------|
| 50 | -34°F | 265°F |
| 60 | -62°F | 270°F |
| 70 | -84°F | 276°F |

*At sea level atmospheric pressure with 15lb. presure cap. The boiling point decreases about 2°F per 1,000 feet of altitude and increases about 2.5°F per pound developed in the system.

**With a 15 psi pressure cap

Boiling Point, Reflux

Flash Point, COC

Total Water, Wt. %

Total Glycols, Wt. %

pH, 50% Volume Solution

Foam Test*

Color

| Part Number | PRAOL3 | Cases Per Pallet | 36 |
|-----------------|--|-----------------------------------|------------------------------------|
| Gallon UPC | 0-74804-03328-1 | Pallets/Cases per Truck | 20/720 |
| Case UPC | 0-74804-13328-8 | Units per Truck | 4,320 |
| Case SCC-14 | 1-00-74804-03328-8 | Truckload Weight* | 44,200lbs. |
| Pack/Unit Case | 6/1 Gallon (3.78 Liters) | Pallet Size | 48"L x 40"W x 53 ^{3/4} "H |
| Weight/Cube | 60 lbs./1.53 cu. ft. | Pallet Weight (inc. A/F & pallet) | 2,210 lbs. |
| Case Dimentions | 15 ^{1/2} "L X 12 ^{1/2} "W X 12 ^{1/4} "H | Cases/Rows High | 9/4 |







PERFORMANCE WITHOUT COMPROMISE

At PEAK, we're the independent guys, running a family owned business that's nothing like Big Oil. Here, American made quality and value go into good, honest products, with everything your engine needs to run right for the long haul.









WWW.PEAKAUTO.COM

HANDLING AND SAFETY INFORMATION Refer to Old World Industries Material Safety Data Sheet (MSDS). The MSDS is available from your PEAK Performance Supplier at www.peakauto.com, or by calling Old World Industries' PEAK technical support line at 1-800-477-5847. We Only Have One World...Please Help Protect It. All laws and regulations should be observed when disposing of Antifreeze/Coolant and Radiator Fluids. Call the EPA or the office of your state or local environmental agency for details on disposal procedures.





Distributed by Old World Industries, LLC Northbrook, IL 60062

p 800.323.5440 www.peakauto.com

©2013 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC. Long Life is a registered trademark of the Warren Distribution



