

## **DESCRIPTION:**

PEAK® COOL 50/50 Antifreeze + Coolant is an orange-colored, ethylene glycol based antifreeze that may be used in all General Motors vehicles requiring DEX-COOL® antifreeze and coolant, newer Ford vehicles requiring Motorcraft specialty orange engine coolant, as well as other automobiles, light duty trucks and motorcycles with aluminum radiators. It's a patened formula that features long lasting inhibitors providing long term protection against damaging rust and corrosion.

## **BENEFITS:**

- Compatible for use in all automobiles, light duty trucks and motorcycles
- Provides 150,000 miles or 5 years of maximum protection when a complete cooling system flush and fill is performed
- Meets European phosphate-free and Japanese silicate-free requirements

Orange

- Prediluted Ready Use formula for topping off
- Meets ASTM D-3306 + ASTM D-4340

## Properties Specific Gravity 60/60°F Boiling Point, Reflux Foam Test\* pH, 50% Volume Solution Flash Point, COC Total Water, Wt. % Total Glycols, Wt. % Color

\*\*With a 15 psi pressure cap

Typical Values	<b>ASTM Test Method</b>
1.055-1.080	D-1122
1.000 1.000	D 1100

1.055-1.080 D-1122 265°F Min.\* D-1120 50 ml./3 sec. Max. B.5 Min-9.20 Max. D-1287 50%, Min. D-92 50% Max. D-1123 50% Min. D-202

N.		5	
üsa	311	IRAN PROPERTY OF THE PROPERTY	
50/50 + C 50/50 DO NOT ADD WATER	FOR USE IN GM	EZE NT  CL  CARS & TRUCKS X-COOL® COOLANT	1 1
ADD WATER WARNING: HARRENS, ON FACE STREET, CANCEL MAN COLOR COLOR COLOR STREET, CANCEL COLOR COLOR COLOR STREET, CANCEL STREET, CAN		One U.S. Gal. (3.78).	

Protection Chart (°F) *Using a 15 psi pressure cap				
Concentration	50%			
Boiling Point*	265°F			
Freezing Point	-34°F			

\*At sea level atmospheric pressure with 15lb. presure cap. The boiling point decreases about 2°F per 1,000 feet of altitude and increases about 2.5°F per pound developed in the system.

Part Number	PRAL53	Cases Per Pallet	36
Gallon UPC	0-74804-03329-8	Pallets/Cases per Truck	20/720
Case UPC	0-74804-13329-5	Units per Truck	4,320
Case SCC-14	1-00-74804-03329-5	Truckload Weight*	44,040lbs.
Pack/Unit Case	6/1 Gallon ( 3.78 Liters)	Pallet Size	48"L x 40"W x 53 <sup>3/4</sup> "H
Weight/Cube	57 lbs./1.53 cu. ft.	Pallet Weight (inc. A/F & pallet)	2,102 lbs.
<b>Case Dimentions</b>	15 <sup>1/2</sup> "L X 12 <sup>1/2</sup> "W X 12 <sup>1/4</sup> "H	Cases/Rows High	9/4







## PERFORMANCE WITHOUT COMPROMISE

At PEAK, we're the independent guys, running a family owned business that's nothing like Big Oil. Here, American made quality and value go into good, honest products, with everything your engine needs to run right for the long haul.





Danica Patrick




Connect with PEAK



WWW.PEAKAUTO.COM

HANDLING AND SAFETY INFORMATION Refer to Old World Industries Material Safety Data Sheet (MSDS). The MSDS is available from your PEAK Performance Supplier at www.peakauto.com, or by calling Old World Industries' PEAK technical support line at 1-800-477-5847. We Only Have One World...Please Help Protect It. All laws and regulations should be observed when disposing of Antifreeze/Coolant and Radiator Fluids. Call the EPA or the office of your state or local environmental agency for details on disposal procedures.





Distributed by Old World Industries, LLC Northbrook, IL 60062 p 800.323.5440 www.peakauto.com

©2013 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC. Long Life is a registered trademark of the Warren Distribution

