

**Mobil HYDRAUL™**

Mobil Commercial Vehicle Lube, Canada

High Performance Multipurpose Tractor Fluid

Product Description

Mobil HYDRAUL™ products are high performance multipurpose tractor lubricants developed for use in agriculture, forestry, mining and construction equipment where a common oil sump is used for the transmission, differential, final drive, wet brake, wet clutch and hydraulic components. The advanced technology in Mobil HYDRAUL products is designed to optimize the performance of agriculture, forestry, mining and construction equipment operating in a wide range of environments and conditions. Mobil HYDRAUL products combine select base oils and an advanced additive package to deliver the varied lubricant performance properties required in severe duty applications of agriculture, forestry, mining and construction equipment drive trains. Mobil HYDRAUL is particularly well suited for reducing wet brake chatter.

Features and Benefits

Mobil HYDRAUL 50 and Mobil HYDRAUL Extra have been specifically developed to ensure good low temperature fluidity for winter operations as low as -35°C. Mobil HYDRAUL 56 oil provides all-season performance down to -25°C.

Mobil HYDRAUL contains anti-wear and extreme pressure additives to provide exceptional protection against wear and scoring to help extend equipment life. Corrosion inhibitors protect against rust and corrosion in wet or humid environments. Potent inhibitors resist oxidation and thermal breakdown to increase the service life of the oil. Anti-foam additives provide resistance to foaming for optimum performance of transmission and hydraulic systems. Mobil HYDRAUL fluids have carefully balanced friction characteristics to provide outstanding wet brake chatter control and clutch operation in a wide range of equipment including John Deere, New Holland, Case and Volvo. Mobil HYDRAUL fluids are compatible with commonly used elastomers, including Viton, for extended seal, gasket, brake and clutch component life.

Features	Advantages and Potential Benefits
Optimum frictional properties	Protects clutches and wet-brakes Outstanding wet brake chatter control
Compatible with latest clutch materials and elastomers, including Viton	Long seal, gasket, brake and clutch component life Reduced oil leakage
High viscosity index and shear stability	Consistent operating response over wide operating range
Excellent protection against rust and corrosion	Protects equipment in wet or humid environments Helps to prevent premature wear
Excellent low temperature properties	Responsive operation and effective lubrication in cold weather applications
Strong anti-wear and extreme pressure properties	Reduces wear, extends equipment life, and reduces maintenance costs
Excellent thermal and oxidation stability	Reduces deposits, extends seal life, and increases service life of equipment and lubricant
Multipurpose capability	Simplifies inventory and reduces misapplication problems
Excellent resistance to foaming	Optimum performance of transmission and hydraulic systems
Good filterability	Keeps systems clean and operating smoothly

Applications

- Agriculture, forestry, mining and construction equipment where a single fluid is recommended for the powershift or hydrostatic transmission, differential, final drive, wet brake, wet clutch and hydraulic components.
- Mobil HYDRAUL 56 is recommended for systems calling for a "heavier" viscosity fluid in summer operation or "all-season" use where temperatures are above -25°C.
- Mobil HYDRAUL 50 is recommended for year-round service in systems calling for a "lighter" viscosity fluid, and as a winter grade in place of HYDRAUL 56 oil in systems operating down to -35°C.
- HYDRAUL EXTRA is an all-season product suitable for the most severe applications over the operating temperature range of -35°C to 100°C.

Specifications and Approvals

This product is recommended by ExxonMobil for use in applications requiring:	MOBIL HYDRAUL 50	MOBIL HYDRAUL 56
API GL-4		X

This product is recommended by Imperial Oil for use in applications requiring:		
AGCO Powerfluid 821 XL		X
FORDNH FNHA-2-C-201.00		X
JOHN DEERE J20C		X
VICKERS 35VQ25	X	X
CATERPILLAR TO-2	X	X
CNH MAT 3505		X
CNH MAT 3525		X
The HFO/1/2 approval is now ba	X	
DENISON HF-1 (T5D & P46 pumps only)	X	
DENISON HF-2 (T5D & P46 pumps only)	X	
JICASE MS 1207		X
JICASE MS 1209		X
JOHN DEERE J20D	X	
MASSEY FERGUSON M-1135		X
MASSEY FERGUSON M-1141		X
Allison C-4		X

This product meets or exceeds the requirements of:		
ZF TE-ML 03E		X

This product meets or exceeds the requirements of:		
ZF TE-ML 05F		X
ZF TE-ML 17E		X
ZF TE-ML 21F		X

Properties and Specifications

Property	MOBIL HYDRAUL 50	MOBIL HYDRAUL 56	MOBIL HYDRAUL EXTRA
ASTM Color, ASTM D1500	L1.5	L2.0	L3.0
Brookfield Viscosity @ -35 C, mPa.s, ASTM D2983	6300	35800	6000
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	19000	140000	12900
Density @ 15 C, kg/l, ASTM D4052			883
Density @ 15.6 C, kg/l, ASTM D4052	877	882	
Flash Point, Cleveland Open Cup, °C, ASTM D92	170	200	170
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	7.25	9.45	9.6
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	34	55	43
Pour Point, °C, ASTM D97	-54	-42	-51

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

HYDRAUL is a trademark of Imperial Oil Limited, Imperial Oil Licensee.

02-2019

Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M

Calgary AB T2P 3 M 9


1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved.