



Power Lube w/PTFE, 312 Grams
 No. 73045 | Item# 1006154 | Case# 1006153

Product Description	Contains PTFE for long-lasting lubrication and protection from friction, wear and corrosion. Helps to increase the operating efficiency of parts and equipment. Can withstand extreme load carrying situations.
Applications	Bearings, gears, linkages, motors, chains, cables, rollers, guide bars, pulleys, cams, valves, ball joints, hinges, slides, cutting tools, taps, dies, pistons, handling equipment, conveyors, hoists, lifts, doors and fans.
Unit Package Description	16 Ounce (473 ml) Aerosol
Brand	CRC
Generic Description 1	High Performance Lubricant with PTFE
Net Fill	312 Grams
UPC Code	078254730455
Unit Dimensions	19.69H x 6.68W x 6.68D cm
Units Per Case	12
Case Dimensions	20.57H x 21.08W x 28.19D cm
Cases Per Pallet	133
Case Weight	5.44 kg
I 2 of 5 Code	30078254730456
Appearance	Light Amber Liquid w/white precipitate
Flash point (F)	<20°F
Flash point (C)	<-6.7°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.863
Plastic Safe	No
Film Type	Wet
Film Thickness	Not Determined
Evaporation Rate	Fast
Dielectric Strength	Not Determined
Working Temp (F)	Max 300°F

Last revised: 10/3/2018
 Page 1 of 2





Working Temp (C)	Max 148.9°C
Propellant	Hydrocarbon
NSF Category Code	H2
NSF Number	154239
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
Restricted from Sale In:	Not for sale in United States.
Removal (How To)	Remove with petroleum solvents or mineral spirits.

Last revised: 10/3/2018
Page 2 of 2