

CHAIN SAW OIL

APRIL CHAIN SAW OIL is a premium quality chain saw oil made with pure virgin base oil and APRIL NANO 1™ lubricant technology for unsurpassed protection and performance. Recommended for chain saws operating under severe conditions. Available in four viscosity grades.



GRADE	FORMAT	LITRES	CODE
light	gallon	4 x 3.7 L	14.8-CHL-SF
	pail	18.9 L	18.9-CHL-SF
	drum	205 L	205-CHL-SF
	tote	1,000 L	900-CHL-SF
	bulk	bulk	100-CHL-SF
medium	gallon	4 x 3.7 L	14.8-CHM-SF
	pail	18.9 L	18.9-CHM-SF
	drum	205 L	205-CHM-SF
	tote	1,000 L	900-CHM-SF
	bulk	bulk	100-CHM-SF
heavy	gallon	4 x 3.7 L	14.8-CHH-SF
	pail	18.9 L	18.9-CHH-SF
	drum	205 L	205-CHH-SF
	tote	1,000 L	900-CHH-SF
	bulk	bulk	100-CHH-SF
heavy +	pail	18.9 L	18.9-CHHP-SF
	tote	1,000 L	900-CHHP-SF

PROPERTY	METHOD	VALUE			
		LIGHT	MEDIUM	HEAVY	HEAVY+
color	visual	amber/red	amber/red	amber/red	amber/red
density @ 15 °C (kg/l)	ASTM D4052	0.8637	0.8664	0.8834	0.8782
water crackle	hot plate	dry	dry	dry	dry
kinematic viscosity @ 40 °C (cSt)	ASTM D445	50 - 60	70 - 80	120 - 130	150
flash point (°C)	ASTM D92	207	228	257	261
pour point (°C)	ASTM D97	-36	-30	-27	-20

