



BAR & CHAIN OIL

Heavy, Medium, Light

Motosel all season Bar & Chain

Motosel all season Bar & Chain is formulated with virgin mineral oil and specific additives for today's high speed chain saws. Contains added Tackifier and higher viscosity base oil for better performance under severe operating conditions.

It acts as a solid film lubricant giving boundary lubrication under apparently dry lubricant conditions and has extreme pressure additives with shock absorbing properties that reduce friction and increase chain life up to 65%. A special penetrating ability provides instant chain lubrication after start up, and a high-tac, no-sling additive helps the lubricant to stay on the chain. A rust inhibitor protects bar and chain during storage.



Applications

All types of chain saws:

- Residential, commercial and industrial chain saws
- Hand operated and automatic oilers
- Adverse operating conditions of the forest products industry
- Chains, bars, and sprockets

TYPICAL CHARACTERISTICS - BAR & CHAIN OIL

GRAVITY, °API	ASTM D 1298	SUMMER	WINTER	EXTREME TAC
Flash Point °C/°F	ASTM D 92	258/496.4	210/410	258/496.4
Pour Point °C/°F	ASTM D 97	-28/-18.4	-38/-36.4	-31/-23.8
Color	ASTM D 1500	4	4	3
Viscosity SUS @ 100°F	ASTM D 88	630	300	750

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



Canadian owned and operated

WWW.MOTOSEL.COM
INFO@MOTOSEL.COM
+1-888-668-6463