

DRY FILM GRAPHITE LUBRICANT



LU™ 204




Medium Pressure Lubricant



NSF® Registered; H2 Rated (Lubricants with no contact) (Registration # 131585)



CONDUCTIVE - DO NOT USE ON ELECTRIC EQUIPMENT



Minimum - Maximum operational temperature range: Low -40 °F (-40 °C) • High 850 °F (454 °C)



HMIS Hazard Rating: Health(2) • Flammability (4) • Reactivity (0)

- Works up to 850°F/1000°F intermittently
- Dries rapidly
- Excellent conductivity
- Coefficient of friction, .123



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 204 Dry Film Graphite Lubricant is a high lubricity graphite that adheres to most surfaces with minimum surface preparation. It air dries rapidly at room temperature to provide clean, long-wearing lubrication. This lube is also conductive and may be used where lubrication and electrical properties are both required. Effective in temperature up to 850°F. constant and 1000°F. intermittent. Low friction coefficient (.123) allows parts to move easily.

LUBRICANTS

USES

- Pre-assembly lubrication of moving parts
- Mechanisms of vending machines and parking meters
- Automotive and industrial gaskets
- Bearings • Chains
- Springs • Locks
- Bushings • Gaskets

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70F.) Shake well before using. Spray at a distance of 10" to 12" from surface.

PERFORMANCE

- PLASTIC SAFE:** No
TEMPERATURE RANGE:
 LOW: -40°F
 HIGH: 850°F constant (1,000°F) intermittent
LOAD CAPACITY: Extreme Pressure
COEFFICIENT OF FRICTION (ASTM D-4518): .123
- NSF Registration Number 131585; H2 Rated
 - Penetrant
 - Water-Displacer
 - Rust Inhibitor

PROPERTIES

- APPEARANCE:** Black
ODOR: Mild solvent
PROPELLANT: Hydrocarbon
WT./GAL.: 5.23
SPECIFIC GRAVITY: 0.63
PAINTABLE: No
% VOC AEROSOL: 99.05%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: Yes
FLASH POINT: <0°F
HAZARD RATING: 2,4,0
SHELF LIFE: 3 years from date of manufacture

RESOURCES

- MSDS/EDS/PRODUCT DATA SHEETS:**
sprayon.com
CUSTOMER SERVICE:
 1-800-777-2966
TECHNICAL INFORMATION:
 1-800-251-2486

PACKAGING

- Stock #: S00204
 UPC Code: 0-75577-90204-0
 Fill Wt.: 10 oz.
 Per Case: 12
 Carton Dimensions:
 L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



LU204



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products
 101 Prospect Ave. NW
 Cleveland, OH 44115
Sprayon.com
 1-800-777-2966

310-PDS-LU204