

SAE 5W-40 **Heavy Duty DIESEL ENGINE OIL**

Motosel CK-4 Full Synthetic Heavy Duty SAE 5W-40 Diesel Engine Oil is a high-performance engine oil designed to meet 2021 and prior model year on-highway and Tier 4 exhaust emission standards. It provides enhanced protection against wear, oxidation, shear viscosity loss, low and high temperature degradation, soot related thickening as well as protection against particulate filter blocking and catalyst poisoning. It is recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane truck, sport utility vehicle, passenger car and other mobile or stationary engines.

Motosel CK-4 Full Synthetic Heavy Duty SAE 5W-40 Diesel Engine Oil meets or exceeds CK-4 / SN service classifications and is compatible with all prior categories. It has been field tested to be comparable to most American, Asian and European manufacturers' standards including ACEA E9, E7, E4, E2, Chrysler/Fiat MS-1092, Ford WSS-M2C171-E, WSS-M2C171-F1, Renault RLD-4, Caterpillar, Detroit Diesel, Allison C-4, MACK, and many other OEM's specifications where a full synthetic SAE 5W-40 CK-4 engine oil is recommended. Always check your owner's manual for proper service recommendations.

Benefits and Applications

- For diesel and gasoline engines
- Full synthetic motor oil outperforms conventional oil
- Demonstrated fuel economy improvement and retention
- Enhanced oxidative stability, emission system and wear protection

Meets the following performance specification :

CK-4 / SN
ACEA E9, E7, E4, E2,
Chrysler/Fiat MS-1092, Ford
WSS-M2C171-E,
WSS-M2C171-F1, Renault
RLD-4, Caterpillar, Detroit
Diesel, Allison C-4, MACK



#M-0253 / 1Qt #M-0419 / 16Gal
 #M-0343 / 4Qt #M-0321 / E-box
 #M-0254 / 5Qt #M-0252 / 55Gal
 #M-0255 / 5Gal #M-0251 / Bulk

TYPICAL CHARACTERISTICS - SAE 5W-40

SAE GRADE	FULL SYN	5W-40
API SERVICE		CK-4 / SN
API Gravity	ASTM D287	35.0
Flash Point, COC °C/°F	ASTM D92	205/401
Pour Point, °C/°F	ASTM D97	-45/-49
Viscosity @ 40°C, cSt	ASTM D445	90.5
Viscosity @ 100°C, cS	ASTM D445	15.0
Viscosity Index	ASTM D2270	145
CCS, mPa-sec °C max	ASTM D5293	6000 @ -30
Total Base No. TBN	ASTM D2896	10.2

Typical test data are average values only. Minor variations, which do not affect performance, may occur. You should consult your owner's manual to verify proper fluid recommendation for your particular vehicle.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



WWW.MOTOSEL.COM
INFO@MOTOSEL.COM
+1-888-668-6463