



---

---

---

# PRODUCT DATA SHEET

Premium Quality Lubricants

## NATIONAL™ CONCRETE FORM OIL

### Architectural Grade Form Oil

### PRODUCT DESCRIPTION

NATIONAL™ CONCRETE FORM oil is designed to meet regulation of VOC emissions from architectural coatings under Section 183 (e) of the Clean Air Act. The VOC content of this product is approximately 350 grams per liter. It is formulated to give excellent, stain-free finish and clean, quick release characteristics. This product affords excellent protection to metal forms from rusting. It meets the requirements for Cleveland Architectural Grade Concrete Form Oil.

### INDUSTRY AND OEM SPECIFICATIONS

- Cleveland Architectural Grade
- VOC emissions (350 grams per liter) Sec 183 (e) Clean Air Act

### APPLICATIONS

NATIONAL™ CONCRETE FORM OIL is a ready to use formula providing a smooth and clean release from concrete forms. Brush, mop, spray or roller can apply this fluid.

### TYPICAL PROPERTIES

ISO GRADE	TEST	Form Oil
Viscosity @100°C	D445	2.0
Pour Point, °C	D97	-50
Color	D1500	L0.5
Flash Point, °F	D92	275
Saponification Number		16.0

PN2008JAN