

PRODRAW 150

GENERAL DESCRIPTION

PRODRAW 150 is a very heavy duty, chlorinated drawing/punch lubricant. It can be used on those jobs requiring a maximum amount of extreme pressure lubrication. PRODRAW 150 will minimize heat build-up in parts and tools and eliminate galling. Its unique additive package ensures excellent performance on a wide variety of deep drawing/punching operations. PRODRAW 150 contains active sulfur and should not be used on copper-based alloys. It contains an effective rust inhibitor package to protect against the staining often associated with chlorinated drawing oils. PRODRAW 150 can be applied by roll, brush, or dip. PRODRAW 150 can be removed using most alkali or caustic cleaners.

TYPICAL PROPERTIES

Viscosity @100°F, SUS.....	2000
Flash Point, °F.....	430
Weight, lbs./gal.	8.66
Chlorine.....	Present
Sulfur.....	Present
Lubricity Esters.....	Present
Color, ASTM.....	3.0

SHIPPING CONTAINERS

Available in 5 gallon pails, 55 gallon drums or 275 gallon bulk containers.

HEALTH & SAFETY

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of this product.

WARRANTY

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.