

LONG LIFE® 50/50 Antifreeze & Coolant

DESCRIPTION:

PEAK® Long Life® 50/50 Prediluted Antifreeze & Coolant features a new coolant technology that is compatible for use in all automobiles and light duty trucks, regardless of make, model, year or original antifreeze color. Its inhibitors provide maximum cooling system protection against damaging rust and corrosion. No need to add water. PEAK Long Life comes Ready to use.

BENEFITS:

- Compatible for use in all automobiles and light duty trucks
- Provides 150,000 miles or 5 years of maximum protection when a complete cooling system flush and fill is performed
- Meets European phosphate free and Japanese silicate free requirements
- Meets ASTM D-3306
- Meets ASTM D-4340



TYPICAL PHYSICAL AND CHEMICAL PROPERTIES:

Properties	Typical Values	ASTM Test Method			
Specific Gravity 60/60°F	1.115-1.124	D-1122			
Boiling Point	265°F Min.*	D-1120	Protection Chart (°F	Protection Chart (°F) *Using a 15 psi pressure cap	
Foam Test	50 ml./3 sec. Max.	D-1881			
pH,	7.5-10.0	D-1287	Comg a 10 por proce	0 045	
Flash Point, COC	50% Min.	D- 92	Concentration	50%	
Total Water, Wt. %	50% Min.	D-1123	Boiling Point*	265	
Total Glycols, Wt. %	50% Max.	D- 202	Freezing Point	-34	
Color	Red		11002119 1 01110	U -F	

^{*} With a 15 psi pressure cap

Part Number	PRER53	Cases Per Pallet	36
Gallon UPC	0-74804-00944-6	Pallets/Cases per Truck	20/720
Case UPC	0-74804-10944-3	Units per Truck	4,320
Case SCC-14	1-00-74804-00944-3	Truckload Weight*	42,040lbs.
Pack/Unit Case	6/1 Gallon (3.78 Liters)	Pallet Size	48"L x 40"W x 53 ^{3/4} "H
Weight/Cube	57 lbs./1.37 cu. ft.	Pallet Weight (inc. A/F & pallet)	2,102 lbs.
Case Dimentions	16"L X 12 ^{1/2} "W X 12 ^{1/4} "H	Cases/Rows High	9/4

(*) Includes Pallet Wt.: 20 @ 50 lbs. ea. = 1,000 lbs. Product Liability Information/Material Safety Data available upon request.

HANDLING AND SAFETY INFORMATION Refer to Old World Industries Material Safety Data Sheet (MSDS). The MSDS is available from your PEAK Performance Supplier at www.peakauto.com, or by calling Old World Industries' PEAK technical support line at 1-800-477-5847. We Only Have One World...Please Help Protect It. All laws and regulations should be observed when disposing of Antifreeze/Coolant and Radiator Fluids. Call the EPA or the office of your state or local environmental agency for details on disposal procedures.



