



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE "930" SERIES

The LUBRIPLATE "930" Series of lubricants are also listed as "multipurpose" but with a higher operating temperature range than the "630" Series. These lubricants possess high film strength and exceptional resistance to water, steam and other adverse operating conditions. Since these lubricants are of the non-melt type, they can be used successfully for high temperature applications up to 375°F and for short intervals up to 400°F.

The LUBRIPLATE "930" Series of lubricants are shear stable multipurpose greases for both plain and anti-friction bearings. These lubricants are recommended wherever Microgel greases or Bentone greases are recommended and used.

LUBRIPLATE No. 930-AAA is an NLGI No. 0 consistency and is ideal and recommended for centralized lubricating systems. This lubricant is also a superior grease for certain types of enclosed gear cases of medium speed and no seals.

LUBRIPLATE NO. 930-AA is an NLGI No. 1 lubricant highly recommended for automatic grease dispensing devices and pressure gun applications. LUBRIPLATE No. 930-AA is available in the convenient 14½-ounce grease-gun cartridge.

LUBRIPLATE No. 930-A is a heavy-body NLGI No. 2.5 lubricant for applications requiring a heavy type product such as grease cups.

LUBRIPLATE No. 930-2 is an NLGI No. 2 lubricant for general grease-gun applications and is also available in the convenient 14½-ounce cartridge.

(Over)

TYPICAL TESTS

| <u>LUBRIPLATE No.</u> | <u>930-AAA</u> | <u>930-AA</u> | <u>930-A</u> | <u>930-2</u> |
|--------------------------------------|-----------------------|----------------------|---------------------|---------------------|
| Type of Thickener | Gelling Agent | Gelling Agent | Gelling Agent | Gelling Agent |
| NLGI No. | 0 | 1 | 2.5 | 2 |
| Worked Penetration Range @ 77°F | 355/385 | 310/340 | 235/260 | 265/295 |
| ASTM Dropping Point | Non-Melt Type | Non-Melt Type | Non-Melt Type | Non-Melt Type |
| Mineral Oil Viscosity SUS @ 100°F | 900 | 750 | 750 | 750 |
| cSt @ 40°C | 167 | 135 | 135 | 135 |
| Color | Off-White | Off-White | Off-White | Off-White |

PART NUMBERS

| <u>Packaging Available</u> | <u>930-AAA</u> | <u>930-AA</u> | <u>930-A</u> | <u>930-2</u> |
|-----------------------------------|-----------------------|----------------------|---------------------|---------------------|
| Carton, 24/14 oz. Cans | L0098-001 | L0096-001 | L0095-001 | ----- |
| Carton, 6/6 lb. Cans | L0098-006 | L0096-006 | L0095-006 | ----- |
| 35 lb. Pail | L0098-035 | L0096-035 | L0095-035 | L0100-035 |
| 120 lb., Quarter Size, Drum | L0098-039 | L0096-039 | L0095-039 | L0100-039 |
| Full Size Drum | L0098-040 | L0096-040 | ----- | L0100-040 |
| Carton, 36/1¾ oz. Tubes (1x6) | ----- | L0096-086 | ----- | ----- |
| Carton, 40/14½ oz. Cartridges | ----- | L0096-098 | ----- | L0100-098 |

Printed in USA
Revised 8-23-10