



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE No. 5555

LUBRIPLATE No. 5555 is an anhydrous calcium, semi-fluid, mild extreme pressure, water repellent fluid lubricant designed for a wide variety of applications.

Typical applications for LUBRIPLATE No. 5555 include:

Automatic lubricating systems especially designed for light fluids or oils usually found on fork lift trucks, trailers, canning and bottling equipment and other similar applications.

Centralized lubricating systems under adverse extreme cold weather conditions.

Gear cases and chain cases of speed reducers, portable tools, transfer cases, etc., especially where noise, leaking or climatic temperature changes vary considerably.

Track rolls for IHC T-6 and TD-6 crawler tractors.

Roller bearing guide pin sleeves (high speed) on machine tools.

Typical tests on LUBRIPLATE No. 5555

Worked Penetration @ 77°F	Semi-Fluid (335/350 30 gram cone) (435/450 converted to standard 150 gram cone)
NLGI No.	000
Soap	Anhydrous Calcium
Mineral Oil Viscosity	
SUS @ 100°F	90
cSt @ 40°C	16
Cold Test of Lubricant	-65°F/-54°C
Color	Off-White

(over)

Cold test characteristics of LUBRIPLATE No. 5555 are excellent

Typical 30 gram cone penetration:	77°F	334
	-40°F	200
Lincoln Ventmeter Tests:	75°F	25 psig
	0°F	50 psig
	-40°F	85 psig

Packaging Available

Part No.

Carton, 4/7 lb. Jugs	L0109-007
Carton, 12/2 lb. Plastic Bottles	L0109-013
35 lb. Pail	L0109-035
120 lb., Quarter Size, Drum	L0109-039
400 lb., Full Size, Drum	L0109-040

Printed in USA
Revised 4-15-08