

ISO-9001 Registered Quality System. ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE CHAIN & CABLE-HEAVY

LUBRIPLATE Chain & Cable-Heavy is a lubricating, penetrating and cleaning lubricant designed for a multitude of heavy-duty applications. LUBRIPLATE Chain & Cable-Heavy will maintain a moist lubricating film that will not pick up dust and dirt but rather will act as a lubricating, cleansing and penetrating agent. In the lubrication of roller chains, it is most important not only to protect the surface of the chains, but also to penetrate and lubricate the inside of the links to provide total lubrication as well as prevention of rust and corrosion both on the inside and the outside.

LUBRIPLATE Chain & Cable-Heavy is designed for medium and large size roller chains, heavy cables, drive chains on concrete mixers as well as other construction equipment and in all areas where an extreme pressure, heavy-duty, tacky, penetrating, lubricating and cleansing film is preferred.

LUBRIPLATE Chain & Cable-Heavy has been used very successfully lubricating chains and slides under steamy wet conditions where other lubricants had failed miserably. Due to its clinging ability, LUBRIPLATE Chain & Cable-Heavy is also recommended for applications where a drip-less oil is required.

Typical Tests

Viscosity SUS @ 100°F	716
cSt @ 40°C	135
Viscosity SUS @ 210°F	78
cSt @ 100°C	15
ISO Grade	150
SAE Grade	40
Flash Point °F/°C	390/199
Fire Point °F/°C	440/227
Pour Point °F/°C	-10/-23
API Gravity	23.5
Color	L-4.5

Packaging Available	Part No.
Carton, 4/7 lb. plastic jugs	L0136-007
Carton, 12/2 lb. plastic bottles	L0136-013
35 lb. pail	L0136-035
120 lb. drum	L0136-039
415 lb. drum	L0136-040