



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE EMB GREASE

LUBRIPLATE EMB Grease is a specially designed polymer type lubricant for all grease type electric motors, pumps, fan motors, as well as other ball and roller bearing applications. LUBRIPLATE EMB Grease is recommended for high-speed, grease type bearings as well as normal speeds.

ADVANTAGES

- Extremely shear stable for extended regreasing intervals.
- Combination of anti-wear and polymer offer extra lubricity thereby reducing heat, frictional drag & power consumption.
- Excellent compatibility with seals, gaskets & plastics.
- Wide ambient temperature operating range.
- Very good water resistance.
- Rust and oxidation inhibited.

Typical Tests

Type of Base	Lithium
Worked Penetration @ 77°F	265-295
NLGI No.	2
ASTM Dropping Point	390°F/199°C
Four Ball E.P. Test,	
Weld Load Kg	315
Rust Test (D-1743)	1
Norma Hoffman Oxidation Bomb Test	3 psi/100 Hours
Mineral Oil	
Viscosity	
SUS @ 100°F	500
cSt @ 40°C	100
Pour Point	-25°F
Aniline Point, °F	201
Color and Character	Off-White and Smooth
Shear Stability	
Penetration 60 Strokes	292
Penetration 10,000 Strokes	300
Penetration 100,000 Strokes	324

(over)

LUBRIPLATE EMB Grease is available in the following:

<u>Packaging Available</u>	<u>Part No.</u>
Carton, 6/6 lb. Cans	L0148-006
35 lb. Pail	L0148-035
120 lb. Quarter Size, Drum	L0148-039
420 lb. Full Size, Drum	L0148-040
Carton, 40/14½ oz. Cartridges	L0148-098