



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE Power Hammer & Chisel Grease

<u>Properties</u>	<u>ASTM Method</u>	<u>Typical Value</u>
NLGI Grade		2
Worked Penetration Range	D-217	265 - 295
Thickener Type		Aluminum Complex
Dropping Point (°F)	D-2265	514°F
4-Ball EP Test	D-2596	
OK Load		520 Kg.
Weld Load		540 Kg.
% Moly Present		1
% Copper Present		2
% Graphite Present		2

Base Oil Properties

Viscosity @ 100°F (SUS)	D-88	1000 SUS
@ 210°F (SUS)	D-88	73 SUS
Flash Point (COC) °F	D-92	420°F

Packaging Available

35 lb. Pail
120 lb., Quarter Size, Drum
Carton, 40 - 14½ oz. Cartridges

Part No's

L0190-035
L0190-039
L0190-098