



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

Sales, Service & Distribution Center  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support  
Phone: 1-800-733-4755

### **LUBRIPLATE Clearplex-2® & LUBRIPLATE Clearplex-1**

Now treated with LUBRI-ARMOUR, LUBRIPLATE's anti-microbial additive developed to prevent the decomposition of lubricants caused by microorganisms. LUBRIPLATE Clearplex greases treated with LUBRI-ARMOUR remain fresh and last longer in harsh food processing plant environments.

\*NSF H1 Registered  
"Certified OU Kosher Pareve"  
"Halal Certified"

LUBRIPLATE Clearplex-2® and LUBRIPLATE Clearplex-1 are **Zinc-Free**, Aluminum Complex thickened, USP White Oil-based, food grade greases. They are manufactured with ingredients that comply with FDA 21 CFR 178.3570 for lubricants with incidental food contact. LUBRIPLATE Clearplex-2® and LUBRIPLATE Clearplex-1 greases are engineered for use in plain and anti-friction bearings in the food-processing industry. They provide outstanding performance in beverage processing machinery such as seamers and closers. Fiske Brothers Refining Company has produced these clear Aluminum Complex-based greases without sacrificing the additive performance package required for good anti-wear, anti-oxidation and water-resistant properties.

<b><u>Typical Tests:</u></b>	<b><u>LUBRIPLATE Clearplex-2®</u></b>	<b><u>LUBRIPLATE Clearplex-1</u></b>
Type of Thickener	Aluminum Complex	Aluminum Complex
Worked Penetration Range	265 - 295	310 - 340
NLGI No.	2	1
Worked Penetration 60 Strokes @ 77°F	280	325
ASTM Dropping Point	505°F / 263°C	464°F / 240°F
Color	Translucent	Translucent
Base Oil Type	USP – FDA 21 CFR 172.878	USP – FDA 21 CFR 172.878
Base Oil Viscosity SUS @ 100°F	850	500
Flash Point	510°F / 266°C	510°F / 266°C
Pour Point	+10°F / -12°C	+10°F / -12°C

(Over)

**LUBRIPLATE Clearplex-2® & LUBRIPLATE Clearplex-1:**

**Features**

Aluminum Complex Base

Water-Resistant

Corrosion Protection

Wear Protection

FDA ingredient-compliant

**Benefits**

Superior Mechanical Stability

Less Washout

Resistant to Acids

Longer Bearing Life

Product and Consumer Safety

<b><u>Packaging Available</u></b>	<b><u>LUBRIPLATE Clearplex-2® Part Numbers</u></b>	<b><u>LUBRIPLATE Clearplex-1 Part Numbers</u></b>
35-lb. Pail	L0351-035	L0350-035
110-lb. Drum	L0351-039	L0350-039
400-lb. Drum	L0351-040	L0350-040
14 oz. Cartridge (40 Per Case)	L0351-098	L0350-098

\*Authorized by NSF for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

\*NSF H1 Registration No. for LUBRIPLATE Clearplex-2® - [129940](#)

\*NSF H1 Registration No. for LUBRIPLATE Clearplex-1 - [140575](#)

(Meets USDA 1998 Guidelines)

\*NSF – National Sanitation Foundation

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

"The LUBRIPLATE Clearplex-2® & LUBRIPLATE Clearplex-1 contain no components derived from TSE/BSE relevant animal species; therefore, they are compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3, July, 2011".