



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE FP-150 & FP-150-L

"These products are certified OU Kosher Pareve"  
"These products are Halal certified"

\*NSF International H-1 Registered  
NSF ISO21469 Certification

## DESCRIPTION

LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L are tacky, waterproof adhesive oils, which will resist heavy water wash down and steam. They are NSF International H-1 Registered oils for use in helical gear boxes, chains, linkages, cams, slides and wherever a drip-less adhesive fluid lubricant is desired.

## APPLICATIONS

- ⇒ Chains, Conveyors, Wire Rope
- ⇒ Peach Pitters – Chain Drivers
- ⇒ Sight Feed Oilers
- ⇒ Scrubbers, Grease Fittings, Chain Drives
- ⇒ Forklifts, Wheel Bearings, Hydraulic Oil Chain Lifts

## ADVANTAGES

- ⇒ Clean, safe, non-toxic lubrication

*\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.*

*"LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L contain no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".*

## STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*	
		FP-150	FP-150-L
<b>Viscosity:</b>			
SUS @ 100°F	ASTM D-2161	1950	510
cSt @ 40°C	ASTM D-445	367	103
SUS @ 210°F	ASTM D-2161	126	67
cSt @ 100°C	ASTM D-445	25	12
Viscosity Index	ASTM D-2270	93	108
API Gravity	ASTM D-287	28.4	30.2
Flash Point	ASTM D-92	395°F/ 202°C	410°F/ 210°C
Fire Point	ASTM D-92	455°F/ 235°C	450°F/ 232°C
Pour Point	ASTM D-97	0°F/ -18°C	-5°F/ -21°C

## PACKAGING AVAILABLE

	<b>FP-150</b>	<b>FP-150-L</b>
55 Gallon Drum	L0735-062	L0736-062
16 Gallon Drum	L0735-061	L0736-061
5 Gallon Pail	L0735-060	L0736-060
Carton, 4/1 Gallon Plastic Jugs	L0735-057	L0736-057
Carton, 12/11 Ounce Aerosol Cans	L0735-063	

**\*NSF International H-1 Registration No.'s**  
(Meets former USDA 1998 Guidelines)

**126123**

**126124**

