



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE HEAT TRANSFER OILS

LUBRIPLATE Heat Transfer Oil is a high viscosity, high flash and fire, extra clean oil, recommended where exceptional heat transfer qualities are desirable. Please note the exceptional high flash point as shown in the tests below:

LUBRIPLATE Heat Transfer Oil is recommended for oil-type heat exchangers used in asphalt plants, roofers' tar kettles, concrete tile and black curing machines and many other similar industrial applications.

Asphalt paving contractors, roofing contractors, concrete block and tile companies are only a few of your potential customers for this fine product.

LUBRIPLATE Heat Transfer Light and LUBRIPLATE Heat Transfer Extra Light are available for applications in which an SAE 20 or SAE 10 grade heat transfer oil is recommended.

LUBRIPLATE Heat Transfer Oils

<u>Typical Tests</u>	<u>Regular</u>	<u>Light</u>	<u>Extra Light</u>
Viscosity SUS @ 210°F	76	56	47
cSt @ 100°C	14	9	6
Viscosity SUS @ 100°F	731	310	180
cSt @ 40°C	135	60	34
Viscosity Index	98	117	122
ISO Grade	150	68	32
SAE Grade	40	20	10
API Gravity	29.5	30.7	31.5
Flash Point, °F/°C	525/274	450/232	425/219
Fire Point, °F/°C	590/310	465/241	450/232
Pour Point, °F/°C	0/-18	-25/-32	-35/-37
Color	3	3	L-1.5

PART NUMBERS

<u>Packaging Available</u>	<u>Regular</u>	<u>Light</u>	<u>Extra Light</u>
5 gallon pail	L0750-060	L0751-060	L0757-060
55 gallon drum	L0750-062	L0751-062	L0757-062