



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105

Phone: 973-589-9150

Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605

Phone: 419-691-2491

Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

**LUBRIPLATE NON-DETERGENT MOTOR OILS**

**LUBRIPLATE Non-Detergent Motor Oils** are high V. I., high flash and fire, extra clean motor oils recommended wherever operating conditions require an oil of this type:

API SA  
Certain Internal Combustion Engines  
Transmissions  
Gear Cases  
AGMA Non-E. P. Gear Oils

**Typical Tests**

<b><u>SAE No.</u></b>	<b><u>10W</u></b>	<b><u>20W-20</u></b>	<b><u>30</u></b>	<b><u>40</u></b>	<b><u>50</u></b>
Viscosity, Saybolt Universal					
SUS @ 210°F	47	56	67	76	103
SUS @ 100°F	180	310	505	731	1,300
Viscosity, Kinematic					
cSt @ 100°C	6	9	12	14	21
cSt @ 40°C	34	60	97	135	245
Viscosity Index	122	117	109	98	97
API Gravity	31.5	30.7	30.1	29.5	27.3
Flash Point, °F/°C	425/219	450/232	485/252	525/274	535/280
Pour Point, °F/°C	-35/-37	-25/-32	-5/-21	0/-18	0/-18
Color	1½-	2-	2½-	3	7-
AGMA Number	1	2	3	4	5

**LUBRIPLATE Non-Detergent Motor Oils** are available in the following:

<b><u>Packaging Available</u></b>	<b><u>10W</u></b>	<b><u>20-W20</u></b>	<b><u>30</u></b>	<b><u>40</u></b>	<b><u>50</u></b>
Carton, 12/1 Quart Plastic	L0804-054	L0806-054	L0807-054	L0808-054	L0809-054
5 Gallon Pail	L0804-060	L0806-060	L0807-060	L0808-060	L0809-060
55 Gallon Drum	L0804-062	L0806-062	L0807-062	L0808-062	L0809-062