

ISO-9001 Registered Quality System. ISO-21469 Compliant.

#### Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

## **PRODUCT DATA**

# LUBRIPLATE SFGO ULTRA 7 SYNTHETIC CHAIN & PENETRATING FLUID

"This product is certified OU Kosher Pareve"

\*NSF International H-1 Registered NSF ISO21469 Certification

## **DESCRIPTION**

LUBRIPLATE SFGO Ultra 7 Synthetic Chain & Penetrating Fluid is a pure PAO-type synthetic, NSF International H-1 registered product with an effective operating temperature range from -50°F to +250°F.

### **APPLICATIONS**

It is an outstanding product to lubricate chains and bearings operating in the food, beverage and pharmaceutical processing industries.

#### **ADVANTAGES**

It will penetrate and protect against rust and corrosion. It will also keep chains clean.

#### **STORAGE RECOMMENDATIONS**

- 1. Products should be stored between 40°F-120°F.
- 2. Products should be stored in a dry covered environment.
- 3. Products should not be stored in warm, direct sunlight.
- 4. improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.











# **Typical Test Data**

| PROPERTY                  | TEST<br>METHOD | TYPICAL<br>RESULTS* |
|---------------------------|----------------|---------------------|
| Viscosity:<br>SUS @ 100°F | ASTM D-2161    | 51                  |
| SUS @ 210°F               | ASTM D-2161    | 34                  |
| cSt @ 40°C                | ASTM D-445     | 7                   |
| cSt @ 100°C               | ASTM D-445     | 2                   |
| Viscosity Index           | ASTM D-2270    | 104                 |
| Pour Point °F/°C          | ASTM D-97      | -65/-54             |
| Flash Point °F/°C         | ASTM D-92      | 305/152             |
| Fire Point °F/°C          | ASTM D-92      | 400/204             |
| API Gravity               | ASTM D-287     | 41.8                |
| Color                     | ASTM D-1500    | 1.0 max             |
| Four Ball Wear Test       | ASTM D-2266    | .4 mm               |
| SAE Grade                 |                | 5W                  |
| ISO Viscosity Grade       |                | 7                   |

# **PACKAGING AVAILABLE**

Part No.

Carton, 12/11 oz. Aerosol Cans

L0912-063

\*NSF International H-1 Registration No.

<u>136601</u>

(Meets former USDA 1998 Guidelines)

\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"LUBRIPLATE SFGO Ultra 7 Synthetic Chain & Penetrating Fluid contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

<sup>&</sup>quot;This product is Halal certified"