00000769

empack

SAFETY DATA SHEET

Empack Spraytech Inc. 98 Walker Drive Brampton, Ontario, L6T 4H6 Canada 905-792-6571

PRODUCT: emzone 12A A/C Oil Charge - 114g

CODE: EM-045852

SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identity Product Item Numbers Manufacturer	emzone 12A A/C Oil Charge - 114g EM-045852 Empack Spraytech Inc. 98 Walker Drive Brampton
	Ontario
	Canada L6T 4H6
	905-792-6571
24 hour emergency telephone number	CANUTEC: (613)-996-6666 collect.
Recommended Use	Universal oil lubricant for A/C systems.
Consumer Commodity Hazard Ratings:	
HMIS	Health: 1 Fire: 4 Reactivity: 0.
-	Health: 1 Fire: 4 Reactivity: 0.
NFPA Rating	Ticalui. TTTTC. + Nedelivily. U.

SECTION 02: HAZARDS IDENTIFICATION

Emergency Overview	Danger. Extremely flammable aerosol. Container is under pressure. Container may explode if heated. Do not puncture. Do not burn. May cause skin and eye irritation. KEEP OUT OF REACH OF CHILDREN .
Potential Health Effects: Skin Contact Eye Contact Ingestion Inhalation	May cause irritation, redness and pain. May be harmful if swallowed.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS		
HAZARDOUS INGREDIENTS	CAS #	WT. %
Lubricating Oil	Mix.	40-70
Isobutane	75-28-5	10-30
Propane	74-98-6	10-30

SECTION 04: FIRST AID MEASURES

Eye Contact	Check for and remove contact lenses. Immediately flush eyes with water for a minimum of
Skin Contact	15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. If irritation or redness develops consult a poison control centre or physician immediately.
Ingestion Inhalation	If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. Move victim to fresh air. If breathing has stopped, give artificial respiration. If heartbeat absent, give external cardiac compression. Monitor breathing and pulse. If symptoms persist, call a physician.
Additional Information	

SECTION 05: FIRE FIGHTING MEASURES

Flammability Class Extinguishing Media	Use extinguishing media appropriate for the surrounding fire. Small Fire: Use Dry
Sensitivity to Mechanical Impact Sensitivity to Static Discharge	

SECTION 06: ACCIDENTAL RELEASE MEASURES

Evacuate and Ventilate the area. Remove all sources of ignition. Wash area with significant quantity of water.



SAFETY DATA SHEET

PRODUCT: emzone 12A A/C Oil Charge - 114g

CODE: EM-045852

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling...... Use with adequate ventilation. Contents under pressure. Do not store in temperatures above 120°F (50°C). Keep away from heat, sparks, and open flames.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	AC TWA	CGIH TLV STEL	PEL	SHA PEL STEL	NIOSH REL
Lubricating Oil	Not available	Not available	Not available	Not available	Not available
Isobutane	800 ppm	1000 ppm	800 ppm	Not available	800 ppm (TWA)
Propane	2,500 ppm	Not available	1,000 ppm	Not available	1,000 ppm
Eye/Face Protectior Skin Protection	1	 Normally, no hand p use chemical resista 	nt gloves conforming	however, prolonged or to appropriate regulation	repeated contact with skin ons. Observe the re provided by the supplier
Respiratory Protecti	on	Not required on a sh	ort-term basis or if ex suitable for organic va	haust ventilation is prov	vided. Use NIOSH
Appropriate Engined	ering Controls	Good general ventila	ation should be used.	Ventilation rates should	d be matched to els below the Threshold
Exposure Limits					

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability Incompatible Materials Conditions to Avoid Hazardous Decomposition Products	
	Has not been reported.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS		LC50	LD50
Lubricating Oil		Not available	Not available
Isobutane		658 mg/L (Rat - 4hrs)	Not available
Propane		658 mg/L (Rat - 4hrs)	Not available
Route of Exposure Effects of Acute Exposure	 Skin contact, Eye contact, Inhalation and Ingestion. Harmful if swallowed or inhaled. Repeated or prolonged contact may cause slight irritation to the skin. May cause irritation to the eyes. 		
Chronic Effects Carcinogenicity	May cause skin defatti	ng and dermatitis.	

Powered by

SAFETY DATA SHEET

PRODUCT: emzone 12A A/C Oil Charge - 114g

SECTION 11: TOXICOLOGICAL INFORMATION

Reproductive Toxicity..... Teratogenicity..... Germ Cell Mutagenicity..... Toxicological Data

No information is available, and no adverse effects are expected. No information is available, and no adverse effects are expected. No information is available, and no adverse effects are expected.

SECTION 12: ECOLOGICAL INFORMATION

Environmental.....

Complete information is not yet available. Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods...... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)	AEROSOLS, Class 2.1, UN1950.
DOT (US-Road)	AEROSOLS, Class 2.1, UN1950, LTD QTY, Consumer commodity ORM-D.
IMDG (International- Marine)	AEROSOLS, Class 2.1, UN1950.
IATA (International- Air)	AEROSOLS, Class 2.1, UN1950, LTD QTY.

SECTION 15: REGULATORY INFORMATION

Canada Regulations:	WHMIS Classification. A: Compressed gas. B5: Flammable Aerosol. CPR (Canadian Controlled Product Regulations): All ingredients are CEPA approved for import to Canada. This product has been classified in accordance with the hazard criteria of the CPR and this SDS contains all information required by CPR. IDL (Canadian Ingredient Disclosure List): Component(s) of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List (section 03). Environmental Protection Act: Constituents of this product are included on the TSCA
Ŭ	inventory. OSHA (29CFR 1910.1200) Classification: Compressed Gas. HIMS Classifications: see section 01.

SECTION 16: OTHER INFORMATION

Disclaimer	The information contained herin is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Empack assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS.
Abbreviations	ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.
Prepared by Latest Revision	



Page 3

CODE: EM-045852