



SAFETY DATA SHEET

1. Identification

Product identifier	Battery Terminal Protector - 212 g
Other means of identification	
Product Code	No. 75046 (Item# 1006303)
Recommended use	Battery terminal protector
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufactured or sold by:	
Company name	CRC Canada Co.
Address	83 Galaxy Blvd Unit 35 - 37 Toronto, ON M9W 5X6 Canada
Telephone	
General Information	416-847-7750
24-Hour Emergency (CHEMTREC)	800-424-9300 (Canada)
Website	www.crc-canada.ca
E-mail	Support.CA@crcindustries.com

2. Hazard identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
	Physical hazards not otherwise classified	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure (oral)	Category 2 (central nervous system, kidney, liver)
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility. May cause damage to organs (central nervous system, kidney, liver) through prolonged or repeated exposure by ingestion. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist or vapor. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid release to the environment.

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire. Collect spillage.

Storage

Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
liquefied petroleum gas		68476-86-8	15 - 40
naphtha (petroleum), hydrotreated light		64742-49-0	15 - 40
heptane, branched, cyclic and linear		426260-76-6	7 - 13
petrolatum		8009-03-8	7 - 13
n-heptane		142-82-5	3 - 7
solvent naphtha (petroleum), light aliph.		64742-89-8	3 - 7
2-methylpentane		107-83-5	1 - 5
3-methylhexane		589-34-4	1 - 5
xylene		1330-20-7	1 - 5
2-methylhexane		591-76-4	0.5 - 1.5
methylcyclohexane		108-87-2	0.5 - 1.5
paraffin oils (petroleum), catalytic dewaxed heavy		64742-70-7	0.5 - 1.5
2,3-dimethylpentane		565-59-3	0.1 - 1
3-ethylpentane		617-78-7	0.1 - 1
ethylbenzene		100-41-4	0.1 - 1
n-hexane		110-54-3	0.1 - 1
water		7732-18-5	0 - 0.1

The exact percentage (concentration) of composition has been withheld as a trade secret.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Edema. Jaundice. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe the mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2,3-dimethylpentane (CAS 565-59-3)	STEL	500 ppm	
	TWA	400 ppm	
2-methylhexane (CAS 591-76-4)	STEL	500 ppm	
	TWA	400 ppm	
2-methylpentane (CAS 107-83-5)	STEL	1000 ppm	
	TWA	500 ppm	
3-ethylpentane (CAS 617-78-7)	STEL	500 ppm	
	TWA	400 ppm	
3-methylhexane (CAS 589-34-4)	STEL	500 ppm	
	TWA	400 ppm	
ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm	
n-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
n-hexane (CAS 110-54-3)	TWA	50 ppm	
	TWA	5 mg/m3	Inhalable fraction.
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)			
petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
2,3-dimethylpentane (CAS 565-59-3)	STEL	2050 mg/m3	
		500 ppm	
	TWA	1640 mg/m3	
		400 ppm	
2-methylhexane (CAS 591-76-4)	STEL	2050 mg/m3	
		500 ppm	
	TWA	1640 mg/m3	
		400 ppm	
2-methylpentane (CAS 107-83-5)	STEL	3500 mg/m3	
		1000 ppm	
	TWA	1760 mg/m3	
		500 ppm	
3-ethylpentane (CAS 617-78-7)	STEL	2050 mg/m3	
		500 ppm	
	TWA	1640 mg/m3	
		400 ppm	
3-methylhexane (CAS 589-34-4)	STEL	2050 mg/m3	
		500 ppm	
	TWA	1640 mg/m3	
		400 ppm	
ethylbenzene (CAS 100-41-4)	STEL	543 mg/m3	
		125 ppm	
	TWA	434 mg/m3	
		100 ppm	
methylcyclohexane (CAS 108-87-2)	TWA	1610 mg/m3	
		400 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m3	
		400 ppm	
n-heptane (CAS 142-82-5)	STEL	2050 mg/m3	
		500 ppm	
	TWA	1640 mg/m3	
		400 ppm	
n-hexane (CAS 110-54-3)	TWA	176 mg/m3	
		50 ppm	
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	1590 mg/m ³	
		400 ppm	
xylene (CAS 1330-20-7)	STEL	651 mg/m ³	
	TWA	150 ppm 434 mg/m ³ 100 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
2,3-dimethylpentane (CAS 565-59-3)	STEL	500 ppm
	TWA	400 ppm
2-methylhexane (CAS 591-76-4)	STEL	500 ppm
	TWA	400 ppm
2-methylpentane (CAS 107-83-5)	TWA	200 ppm
	STEL	500 ppm
3-ethylpentane (CAS 617-78-7)	STEL	500 ppm
	TWA	400 ppm
3-methylhexane (CAS 589-34-4)	STEL	500 ppm
	TWA	400 ppm
ethylbenzene (CAS 100-41-4)	TWA	20 ppm
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
n-hexane (CAS 110-54-3)	TWA	20 ppm
xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
2,3-dimethylpentane (CAS 565-59-3)	STEL	500 ppm	
	TWA	400 ppm	
2-methylhexane (CAS 591-76-4)	STEL	500 ppm	
	TWA	400 ppm	
2-methylpentane (CAS 107-83-5)	STEL	1000 ppm	
	TWA	500 ppm	
3-ethylpentane (CAS 617-78-7)	STEL	500 ppm	
	TWA	400 ppm	
3-methylhexane (CAS 589-34-4)	STEL	500 ppm	
	TWA	400 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm	
n-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
n-hexane (CAS 110-54-3)	TWA	50 ppm	
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.
petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
2,3-dimethylpentane (CAS 565-59-3)	STEL	500 ppm	
	TWA	400 ppm	
2-methylhexane (CAS 591-76-4)	STEL	500 ppm	
	TWA	400 ppm	
2-methylpentane (CAS 107-83-5)	STEL	1000 ppm	
	TWA	500 ppm	
3-ethylpentane (CAS 617-78-7)	STEL	500 ppm	
	TWA	400 ppm	
3-methylhexane (CAS 589-34-4)	STEL	500 ppm	
	TWA	400 ppm	
ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
methylcyclohexane (CAS 108-87-2)	TWA	400 ppm	
n-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
n-hexane (CAS 110-54-3)	TWA	50 ppm	
xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
2-methylpentane (CAS 107-83-5)	STEL	3500 mg/m3	
		1000 ppm	
		1760 mg/m3	
ethylbenzene (CAS 100-41-4)	STEL	500 ppm	
		543 mg/m3	
		125 ppm	
	TWA	434 mg/m3	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
methylcyclohexane (CAS 108-87-2)	TWA	100 ppm	
		1610 mg/m3	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 ppm	
		1590 mg/m3	
n-heptane (CAS 142-82-5)	STEL	400 ppm	
		2050 mg/m3	
n-hexane (CAS 110-54-3)	TWA	500 ppm	
		1640 mg/m3	
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	STEL	400 ppm	
		176 mg/m3	
petrolatum (CAS 8009-03-8)	STEL	50 ppm	Mist.
		10 mg/m3	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	5 mg/m3	Mist.
		1590 mg/m3	
xylene (CAS 1330-20-7)	STEL	400 ppm	
		651 mg/m3	
	TWA	150 ppm	
		434 mg/m3	
		100 ppm	

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
2-methylpentane (CAS 107-83-5)	15 minute	1000 ppm
	8 hour	500 ppm
ethylbenzene (CAS 100-41-4)	15 minute	125 ppm
	8 hour	100 ppm
methylcyclohexane (CAS 108-87-2)	15 minute	500 ppm
	8 hour	400 ppm
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	15 minute	500 ppm
	8 hour	400 ppm
n-heptane (CAS 142-82-5)	15 minute	500 ppm
	8 hour	400 ppm
n-hexane (CAS 110-54-3)	15 minute	62.5 ppm
	8 hour	50 ppm
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	15 minute	10 mg/m3

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
	8 hour	5 mg/m ³
petrolatum (CAS 8009-03-8)	15 minute	10 mg/m ³
	8 hour	5 mg/m ³
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	15 minute	500 ppm
	8 hour	400 ppm
xylene (CAS 1330-20-7)	15 minute	150 ppm
	8 hour	100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
n-hexane (CAS 110-54-3)	0.5 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*
xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

n-hexane (CAS 110-54-3) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

n-hexane (CAS 110-54-3) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

n-hexane (CAS 110-54-3) Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

n-hexane (CAS 110-54-3) Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

n-hexane (CAS 110-54-3) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

n-hexane (CAS 110-54-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

n-hexane (CAS 110-54-3) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton rubber (fluor rubber).

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Not available.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Aerosol.
Color	Dark red.
Odor	Petroleum.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-131.1 °F (-90.6 °C) estimated
Initial boiling point and boiling range	118.4 °F (48 °C) estimated
Flash point	< 0 °F (< -17.8 °C)
Evaporation rate	Fast.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1 % estimated
Flammability limit - upper (%)	8 % estimated
Vapor pressure	1447.6 hPa estimated
Vapor density	Not available.
Relative density	0.73
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	489.2 °F (254 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Percent volatile	65.7 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information**Information on likely routes of exposure**

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.

Ingestion

May cause damage to organs through prolonged or repeated exposure by ingestion. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Edema. Jaundice.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
3-methylhexane (CAS 589-34-4)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 20 mg/l, 4 hours
Oral		
LD50	Rat	> 2000 mg/kg
ethylbenzene (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	15400 mg/kg
Oral		
LD50	Rat	3500 mg/kg
heptane, branched, cyclic and linear (CAS 426260-76-6)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 60 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg
methylcyclohexane (CAS 108-87-2)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 4000 mg/kg
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
n-heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	3000 mg/kg

Components	Species	Test Results
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 73.5 mg/l, 4 hours
Oral		
LD50	Rat	25000 mg/kg
n-hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 1300 mg/kg
Oral		
LD50	Rat	15840 mg/kg
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
petrolatum (CAS 8009-03-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
Oral		
LD50	Rat	> 3000 mg/kg
xylene (CAS 1330-20-7)		
Acute		
Dermal		
LD50	Rabbit	> 4300 mg/kg
Inhalation		
LC50	Rat	29 mg/l, 4 hours

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.
ACGIH Carcinogens	
ethylbenzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.

paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)
 petrolatum (CAS 8009-03-8)
 xylene (CAS 1330-20-7)

A4 Not classifiable as a human carcinogen.
 A4 Not classifiable as a human carcinogen.
 A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

ethylbenzene (CAS 100-41-4)
 paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)
 petrolatum (CAS 8009-03-8)
 xylene (CAS 1330-20-7)

Confirmed animal carcinogen with unknown relevance to humans.
 Not classifiable as a human carcinogen.
 Not classifiable as a human carcinogen.
 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

ethylbenzene (CAS 100-41-4)
 xylene (CAS 1330-20-7)

2B Possibly carcinogenic to humans.
 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Suspected of damaging fertility.
Specific target organ toxicity - single exposure May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure May cause damage to organs (central nervous system, kidney, liver) through prolonged or repeated exposure by ingestion.
Aspiration hazard May be fatal if swallowed and enters airways.
Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Components	Species	Test Results
2-methylpentane (CAS 107-83-5)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50 Daphnia	1 - 10 mg/l, 48 hours
Fish	LC50 Fish	1 - 10 mg/l, 96 hours
ethylbenzene (CAS 100-41-4)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50 Daphnia magna	1.8 mg/l, 48 hours
Fish	LC50 Fish	5.1 mg/l, 96 hours
heptane, branched, cyclic and linear (CAS 426260-76-6)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50 Water flea (Daphnia magna)	1.5 mg/l, 48 hours
methylcyclohexane (CAS 108-87-2)		
Aquatic		
Fish	LC50 Striped bass (Morone saxatilis)	5.8 mg/l, 96 hours
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50 Daphnia	1 - 10 mg/l, 48 hours
Fish	LC50 Fish	1 - 10 mg/l, 96 hours
n-heptane (CAS 142-82-5)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50 Water flea (Daphnia magna)	1.5 mg/l, 48 hours
Fish	LC50 Fathead minnow (Pimephales promelas)	2.1 - 2.98 mg/l, 96 hours

Components	Species	Test Results
n-hexane (CAS 110-54-3)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2.101 - 2.981 mg/l, 96 hours
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 8.8 mg/l, 96 hours
		8.8 mg/l, 96 hours
<i>Acute</i>		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.5 mg/l, 48 hours
xylene (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 6.702 - 10.032 mg/l, 96 hours
<i>Acute</i>		
Crustacea	EC50	<i>Daphnia magna</i> 3.82 mg/l, 48 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-methylpentane	3.74
ethylbenzene	3.15
methylcyclohexane	3.61
n-heptane	4.66
n-hexane	3.9
xylene	3.12 - 3.2

Bioconcentration factor (BCF)

ethylbenzene	1
naphtha (petroleum), hydrotreated light	10 - 25000
xylene	23.99

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Contents under pressure. Do not puncture, incinerate or crush. Empty container can be recycled. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.



14. Transport information

TDG

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	80, 107

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity

Transport hazard class(es)**Class** 2.1**Subsidiary risk** -**Packing group** Not applicable.**ERG Code** 10L**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Other information****Passenger and cargo aircraft** Allowed with restrictions.**Cargo aircraft only** Allowed with restrictions.**IMDG****UN number** UN1950**UN proper shipping name** AEROSOLS, Limited Quantity**Transport hazard class(es)****Class** 2.1**Subsidiary risk** -**Packing group** Not applicable.**Environmental hazards****Marine pollutant** Yes, but exempt from the regulations.**EmS** F-D, S-U**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**IATA****IMDG; TDG**

15. Regulatory information**Canadian regulations****Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

ethylbenzene (CAS 100-41-4)

xylene (CAS 1330-20-7)

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	07-29-2019
Version #	01
Further information	CRC # 597P-Q/1002627-1002629
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co..
Revision information	Product and Company Identification: Product Codes Hazard identification: Prevention Hazard identification: Response Hazard identification: GHS Symbols Hazard identification: Other hazards Accidental release measures: Personal precautions, protective equipment and emergency procedures Accidental release measures: Methods and materials for containment and cleaning up Handling and storage: Precautions for safe handling Handling and storage: Conditions for safe storage, including any incompatibilities Physical & Chemical Properties: Multiple Properties Transport Information: Agency Name, Packaging Type, and Transport Mode Selection GHS: Classification