



# SAFETY DATA SHEET

## SECTION 1) IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

**Product ID:** 588713  
**Product Name:** Xtreme SAE 80W-90 GL-5 LS Gear Oil  
**Revision Date:** Jun 21, 2019 **Date Printed:** Aug 15, 2019  
**Version:** 5.0 **Supersedes Date:** Mar 19, 2018  
**Manufacturer's Name:** Martin Operating Partnership L.P.  
**Address:** P.O. Box 191, Kilgore, TX, US, 75663  
**Emergency Phone:** CHEMTREC (800) 424-9300  
**Information Phone Number:** 870-864-7800  
**Fax:**  
**Product/Recommended Uses:** Auto Gear Oil

## SECTION 2) HAZARDS IDENTIFICATION

### Classification

Skin Irritation - Category 3

### Pictograms

None

### Signal Word

Warning

### Hazardous Statements - Health

H316 - Causes mild skin irritation

### Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

### Precautionary Statements - Prevention

No precautionary statement available.

### Precautionary Statements - Response

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

### Precautionary Statements - Storage

No precautionary statement available.

### Precautionary Statements - Disposal

No precautionary statement available.

### Physical Hazards Not Otherwise Classified (PHNOC)/Health Hazards Not Otherwise Classified (HHNOC)

None.

## SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0064742-65-0	MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC	45.0% - 70.0%
Trade Secret	SULFURIZED ISOBUTYLENE	1.0% - 5.0%
Trade Secret	DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (DMSO <3%)	1.0% - 5.0%
N/A	REACTION PRODUCT OF PHOSPHORIC ACID MONO- OR DI-(C6-C10) ALKYLESTER WITH ALKYLAMINE	0.1% - 1.0%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## SECTION 4) FIRST-AID MEASURES

### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.

### Skin Contact

Rinse/wash with lukewarm, gently flowing water and mild soap for 5 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

### Eye Contact

If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

### Ingestion

Immediately call a POISON CENTER/doctor. If exposed or concerned: Get medical advice/attention.

### Most Important Symptoms/Effects, Acute and Delayed

No data available.

### Indication of Immediate Medical Attention and Special Treatment Needed

No data available.

## SECTION 5) FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide water spray or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

### Unsuitable Extinguishing Media

Do not use water in a jet.

### Specific Hazards in Case of Fire

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke), carbon monoxide, unidentified organic and inorganic compounds.

Oxides of C, S and N. Additional byproducts include hydrogen sulfide, alkyl mercaptan and other sulfides.

Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. Heavy flammable vapors may settle along ground level and low spots to create an invisible fire hazard. The vapors may extend to sources of ignition and flash back.

### Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray or fog may be useful in minimizing or dispersing vapors and to protect personnel.

### Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## SECTION 6) ACCIDENTAL RELEASE MEASURES

## Emergency Procedure

Immediately turn off or isolate any source of ignition. Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material.

Large spills, once contained, may be picked up using explosion proof, non sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. Local authorities should be advised if significant spillages cannot be contained.

Spill procedures (water): Remove from surface by skimming or with suitable adsorbents. If a large spill occurs notify appropriate authorities.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

## Recommended equipment

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

## Personal Precautions

Avoid breathing vapor or mist. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

## Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

## Methods and Materials for Containment and Cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

# SECTION 7) HANDLING AND STORAGE

## General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Do not swallow.

Wear appropriate respirator when ventilation is inadequate.

Do not enter storage areas and confined spaces unless adequately ventilated.

Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

## Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

## Storage Room Requirements

Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.

# SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

## Eye protection

Wear indirect-vent, impact and splash resistant goggles when working with liquids. Wear eye protection with side shields or goggles. If additional protection is needed for entire face, use in combination with a face shield.

## Skin protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter

suitable for combined particulate/organic gases and vapours.

### Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of gas, vapors or dusts below their respective threshold limit value.

Chemical Name	CAN_ONtmg	CAN_ONtppm	CAN_ONsmg	CAN_ONsppm	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)
MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC					[(L)]; [5 (l)];	(L)		

Chemical Name	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen
MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC	[A2]; [A4];	URT irr	[A2]; [A4];	2000	500			

Chemical Name	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC		1					

The information in this Section does not list components that might have relevant OSHA Tables (Z1, Z2, Z3) , OSHA TWA (mg/m3), OSHA TWA (ppm) regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

Density	7.49 lb/gal
% Solids By Weight	8.29%
Density VOC	0.00 lb/gal
% VOC	0.00%
Specific Gravity	0.90

---

Appearance	Amber, clear fluid
Odor Threshold	N.A.
Odor Description	Mild petroleum hydrocarbon odor
pH	N.A.
Water Solubility	Negligible in water
Flammability	Flash point at or above 200°F/93°C
Flash Point Symbol	N.A.
Flash Point	243 °C (469 °F)
Viscosity	176.1 cSt at 40°C (104°F) or 15.4 cSt at 100°C (212°F)
Lower Explosion Level	N.A.
Upper Explosion Level	N.A.
Vapor Pressure	N.A.

Vapor Density	>1 at STP
Freezing Point	N.A.
Melting Point	N.A.
Low Boiling Point	Expected to be > 260°C (500°F)
High Boiling Point	N.A.
Auto Ignition Temp	N.A.
Decomposition Pt	N.A.
Evaporation Rate	Negligible at STP
Coefficient Water/Oil	N.A.

## SECTION 10) STABILITY AND REACTIVITY

### Stability

Stable

### Conditions to Avoid

Avoid direct sunlight, extremes of temperatures and contact with incompatible materials.

Avoid high temperatures and product contamination.

### Hazardous Polymerization

Will not occur.

### Incompatible Materials

Strong oxidizing agents.

### Hazardous Decomposition Products

Smoke, carbon monoxide and dioxide and other aldehydes of incomplete combustion. Oxides of C, N and S. Hydrogen sulfide and alkyl mercaptans and other sulfides may be released.

## SECTION 11) TOXICOLOGICAL INFORMATION

### Likely route of exposure

Inhalation, ingestion, skin absorption (In most cases)

### Skin Corrosion/Irritation

Causes mild skin irritation

### Serious Eye Damage/Irritation

Avoid prolonged contact with the eyes, which may cause mild eye discomfort, tearing, or blurring of vision.

No data available.

### Respiratory or Skin Sensitization

Prolonged or repeated contact may lead to an allergic skin sensitization in some people and dermatitis (dryness, chapping and reddening of skin).

### Respiratory/Skin Sensitization

No data available.

### Carcinogenicity

The highly refined mineral oil contains <3% DMSO extract as measured by IP 346, hence the classification of a carcinogen need not apply.

### Germ Cell Mutagenicity

No data available.

### Reproductive Toxicity

No data available.

### Specific Target Organ Toxicity - Single Exposure

No data available.

### Specific Target Organ Toxicity - Repeated Exposure

No data available.

**Aspiration Hazard**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

No data available.

**Acute Toxicity**

If inhalation : Overexposure by inhalation of hot material may cause nonspecific discomfort, such as nausea, headache or weakness. Caution should be taken to prevent forming aerosol or misting of this product without proper respiratory protection.

No data available.

0064742-65-0 MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC

LD50 (Rodent - rat, Oral) : >5000 mg/kg, Toxic effects : Details of toxic effects not reported other than lethal dose value.

LD50 (Rodent - rabbit, Administration onto the skin) : 5000 mg/kg, Toxic effects : Details of toxic effects not reported other than lethal dose value.

**SECTION 12) ECOLOGICAL INFORMATION**

**Toxicity**

No data available.

**Persistence and Degradability**

No Data Available.

**Bio-accumulative Potential**

CAS 64742-65-0 Mineral Oil, Petroleum Distillates, Solvent-Dewaxed Heavy Paraffinic : Contains constituents with the potential to bioaccumulate.

**Other Adverse Effects**

No Data Available.

**Mobility in Soil**

0064742-65-0 MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC

Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.

**SECTION 13) DISPOSAL CONSIDERATIONS**

**Waste Disposal**

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

**SECTION 14) Transport Information**

	<b>IATA Information</b>	<b>IMDG Information</b>	<b>Transport Canada</b>	<b>U.S. DOT Information</b>
<b>UN number:</b>	Not Regulated	Not Regulated	Not Regulated	Not Regulated
<b>Proper shipping name:</b>	N/A	N/A	N/A	N/A
<b>Hazard class:</b>	Not Applicable	Not Applicable	Not Applicable	Not Applicable
<b>Packaging group:</b>	Not Applicable	Not Applicable	Not Applicable	Not Applicable
<b>Hazardous substance (RQ):</b>			No Data Available	No Data Available
<b>Marine Pollutant:</b>		No Data Available	No Data Available	No Data Available

Note / Special Provision:	No Data Available	No Data Available	No Data Available	No Data Available
Toxic-Inhalation Hazard:			No Data Available	No Data Available

## SECTION 15) REGULATORY INFORMATION


### Safety, health and environmental regulations

CAS	Chemical Name	% By Weight	Regulation List
0064742-65-0	MINERAL OIL, PETROLEUM DISTILLATES ,SOLVENT DEWAXED HEAVY PARAFFINIC	45.0%- 70.0%	DSL, TX_ESL, SARA 312, TSCA

## SECTION 16) OTHER INFORMATION INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS

### Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.



### Version 5.0:

Revision Date: Jun 21, 2019

Changes made to Section 1, 2, 3, 6, 8, 9, 14, 15 and 16. Please contact the supplier for further information on the version history.

## DISCLAIMER

Information provided in this Safety Data Sheet is considered accurate and reliable based on information issued from internal and outside sources to the best of Martin Operating Partnership L.P.'s knowledge; however, Martin Operating Partnership L.P. makes no representations, guarantees or warranties, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such information or the result to be obtained from the use thereof or as to the sufficiency of information herein presented. Martin Operating Partnership L.P. assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.

This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Martin Operating Partnership L.P., must rely upon information provided by the material manufacturers or distributors.