

# SAFETY DATA SHEET General Purpose FG Silicone Spray

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

#### 1. Identification

#### **Product identifier**

**Product name** General Purpose FG Silicone Spray

Product number L0723-063

NSF Registration Number 126086

#### Recommended use of the chemical and restrictions on use

Restriction on use Lubricant.

Uses advised against No specific uses advised against are identified.

#### Details of the supplier of the safety data sheet

Manufacturer Lubriplate Lubricants Co.

Corporate Headquarters 129 Lockwood Street Newark, NJ 07105

Midwest Office & Plant 1500 Oakdale Ave. Toledo, OH 43605 419-691-2491 419-693-3806

## Emergency telephone number

Emergency telephone Chem-Tel: 1-800-255-3924 (US & Canada only)

01-813-248-0585 (Outside US & Canada)

#### 2. Hazard identification

#### Classification of the substance or mixture

Physical hazards Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 STOT SE 3 - H336 Asp. Tox. 1 - H304

Environmental hazards Not Classified

Label elements

#### Hazard pictograms









Signal word

Danger

Hazard statements H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTRE/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label).

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place. P412 Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

#### Contains

Naphtha (petroleum), light alkylate, acetone

#### Other hazards

This product does not contain any substances classified as PBT or vPvB.

#### 3. Composition/information on ingredients

#### **Mixtures**

#### Naphtha (petroleum), light alkylate

10-30%

CAS number: 64741-66-8

#### Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304

## General Purpose FG Silicone Spray

acetone 10-30%

CAS number: 67-64-1

#### Classification

Flam. Liq. 2 - H225 Eye Irrit. 2A - H319 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

\* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

#### 4. First-aid measures

#### Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical

personnel.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery

position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if

the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical

attention if symptoms are severe or persist.

**Skin contact** Rinse with water.

**Eye contact** Rinse with water. Do not rub eye. Remove any contact lenses and open eyelids wide apart.

Get medical attention if any discomfort continues.

**Protection of first aiders** First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

**Inhalation** A single exposure may cause the following adverse effects: Headache. Nausea, vomiting.

Central nervous system depression. Drowsiness, disziness, disorientation, vertigo. Narcotic

effect.

**Ingestion** Due to the physical nature of this product, it is unlikely that ingestion will occur. Aspiration

hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical

pneumonitis.

Skin contact Redness. Irritating to skin.

**Eye contact** Irritating to eyes.

Indication of any immediate medical attention and special treatment needed

#### 5. Fire-fighting measures

#### **Extinguishing media**

## General Purpose FG Silicone Spray

Suitable extinguishing media

The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder

or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

#### Specific hazards arising from the hazardous product

Specific hazards

Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Vapours may form explosive mixtures with air.

Hazardous combustion products

Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

#### Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

#### **Environmental precautions**

**Environmental precautions** 

Avoid discharge into drains or watercourses or onto the ground.

#### Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

#### Reference to other sections

#### Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

#### 7. Handling and storage

#### Precautions for safe handling

#### Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

## Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

#### Conditions for safe storage, including any incompatibilities

#### Storage precautions

Store away from incompatible materials (see Section 10). Store locked up. Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F.

#### Storage class

Chemical storage.

#### Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.

## 8. Exposure controls/Personal protection

#### **Exposure controls**

## Protective equipment







## Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.

#### Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

#### Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and any relevant provincial regulation relating to health and safety at work. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

## General Purpose FG Silicone Spray

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

**Hygiene measures** Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke

when using this product.

Respiratory protection Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH

approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Full face mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial

regulation relating to health and safety at work.

Environmental exposure

controls

Keep container tightly sealed when not in use.

#### 9. Physical and chemical properties

#### Information on basic physical and chemical properties

**Appearance** Liquid. Aerosol.

Colour Clear.

Odour Mild.

Odour thresholdNot available.pHNot available.Melting pointNot available.

Flash point -18°C/-0.4°F Closed cup. [Propellant]

Not available.

**Evaporation rate** Not available.

**Flammability (solid, gas)** Extremely flammable aerosol.

Upper/lower flammability or

Initial boiling point and range

explosive limits

Lower flammable/explosive limit: 0.9% Upper flammable/explosive limit: 9.5%

Other flammability Heat of Combustion (kJ/g):  $\geq 30$ 

Vapour pressure 723.9 kPa @ 50°C

Vapour density > 1

Relative density 0.97

Solubility(ies) Insoluble in water.

Partition coefficientNot available.Auto-ignition temperatureNot available.Decomposition TemperatureNot available.ViscosityNot available.

**Explosive properties** Not applicable.

## General Purpose FG Silicone Spray

Oxidising properties Not available.

Other information None.

10. Stability and reactivity

**Reactivity** See the other subsections of this section for further details.

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidizing agents.

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurized

container: may burst if heated

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

#### 11. Toxicological information

#### Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC50) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitization

**Respiratory sensitization** Based on available data the classification criteria are not met.

Skin sensitization

**Skin sensitization** Based on available data the classification criteria are not met.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

**IARC carcinogenicity**None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

## General Purpose FG Silicone Spray

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the

result if vomited material containing solvents reaches the lungs.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

**Inhalation** A single exposure may cause the following adverse effects: Headache. Nausea, vomiting.

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic

effect.

**Ingestion** Due to the physical nature of this product, it is unlikely that ingestion will occur. Aspiration

hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical

pneumonitis.

Skin contact Redness. Irritating to skin.

**Eye contact** Irritating to eyes.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs Central nervous system

12. Ecological information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

**Toxicity** Based on available data the classification criteria are not met.

Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

#### General information

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

#### Disposal methods

Do not empty into drains. Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents.

## 14. Transport information

General For limited quantity packaging/limited load information, consult the relevant modal

documentation using the data shown in this section.

**DOT transport notes** As supplied, this product is consigned under the Limited Quantities provisions.

**UN number** 

**UN No. (TDG)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

**UN No. (DOT)** UN1950

UN proper shipping name

Proper shipping name (TDG) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (DOT) AEROSOLS

## Transport hazard class(es)

DOT class 2.1

DOT hazard label 2.1

TDG class 2.1

TDG label(s) 2.1

IMDG class 2.1

ICAO class/division 2.1

#### Transport labels



#### **DOT transport label**



## General Purpose FG Silicone Spray

#### Packing group

TDG packing group None

IMDG packing group None

ICAO packing group None

DOT packing group None

#### **Environmental hazards**

#### Environmentally hazardous substance/marine pollutant

No.

#### Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-D, S-U

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## 15. Regulatory information

#### **Inventories**

#### Canada - DSL/NDSL

All the ingredients are listed or exempt.

Petroleum gases, liquefied, sweetened

Naphtha (petroleum), light alkylate

Dimethyl siloxane

#### 16. Other information

Classification abbreviations

and acronyms

Aerosol = Aerosol

Eye Irrit. = Eye irritation

Skin Irrit. = Skin irritation

STOT SE = Specific target organ toxicity-single exposure Press. Gas (Comp.) = Gas under pressure: Compressed gas

**Training advice** Only trained personnel should use this material.

Revision date 2020-06-23

Revision 1

Supersedes date 2018-07-09

SDS number 5162

Hazard statements in full H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### End of SDS

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.