00	00)1	561
00	00		

spraytech inc.

SAFETY DATA SHEET

Empack Spraytech Inc. 98 Walker Drive Brampton, Ontario, L6T 4H6 Canada 905-792-6571

PRODUCT: emzone A/C Cool Refrigerant 1234yf Replacement - 170 g (6 oz.)

CODE: EM-045830

SECTION 01: IDENTIFICATION

Product Item Numbers Product Identity Manufacturer	emzone A/C Cool Refrigerant 1234yf Replacement - 170 g (6 oz.)
24 hour emergency telephone number	In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800) 424-9300.
Recommended Use Chemical Family	Environmental friendly refrigerant. Hydrocarbon blend.

SECTION 02: HAZARD IDENTIFICATION



Label Elements:	
Signal Word	DANGER.
Hazard Classification:	
	Flammable Aerosols - Category 1. Gases Under Pressure - Compressed gas.
Health Hazards	Not Classified.
Environmental Hazards	Not Classified.
Hazard Statement	H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated (1). H280:Contains gas under pressure; may explode if heated (C).
Precautionary Statements:	
Prevention	P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use.
Response	None .
Storage	P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. P403:Store in a well ventilated place.
Disposal	P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.
Hazard(s) not otherwise classified (HNOC)	None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS CHEMICAL NAME AND SYNONYMS CAS # WT. % Propane 74-98-6 40-70 Isobutane 75-28-5 15-40

SECTION 04: FIRST-AID MEASURES

Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain
Skin Contact	immediate medical assistance. Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20
	minutes. Consult a poison control centre or physician immediately.
Eye Contact	Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.
Ingestion	Ingestion is unlikely to occur. If swallowed do not induce vomiting because of risk of
ingeotion	aspiration into the lungs. If aspiration is suspected obtain immediate medical attention.
Most important symptoms/effects, acute	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct
and delayed	contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may
	cause headache, fatique, dizziness and nausea. May cause redness and pain.



Page 2

PRODUCT: emzone A/C Cool Refrigerant 1234yf Replacement - 170 g (6 oz.)

SECTION 04: FIRST-AID MEASURES

Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
SECTI	ON 05: FIRE-FIGHTING MEASURES

General Fire Hazards Suitable Extinguishing Media	Dry chemical powder. Carbon dioxide. Foam, water spray or fog.
Unsuitable Extinguishing Media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific Hazards Arising from the Chemica	al In case of fire, the following can be released: Carbon Oxides (CO, CO2), Other unidentified
	Organic Compounds.
Special Protective Equipment and	Firefighters must use standard protective equipment including flame retardant coat, helmet
Precautions for Firefighters	with water to prevent vapor pressure build up. For massive fire in cargo area, use
	unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures Methods and Materials for Containment and Cleaning Up	Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Non-sparking tools should be used.
Environmental Precautions	Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.
Conditions for Safe Storage including any Incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	A(TWA	CGIH TLV STEL	OSH/ PEL	A PEL STEL	NIOSH REL
Propane	Not available	Not available	1,000 ppm	Not available	Not available
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available
Appropriate Engineering Individual Protection Mea Eye/Face Protection Skin Protection Respiratory Protection Thermal Hazards General Hygiene Conside	Isures:	Local exhaust ventilation of Value if unprotected perso Chemical splash goggles Chemical resistant gloves appropriate chemical resis Use approved NIOSH res None Known. When using, do not eat, d such as washing after har Routinely wash work cloth	onnel are involved. are recommended. are recommended. A stant clothing. pirators for emergenci rink or smoke. Always adling the material and	void contact with the ski es. observe good personal before eating, drinking	n. Wear hygiene measures,

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Powered by

ecis

SAFETY DATA SHEET

CODE: EM-045830

Page 3

PRODUCT: emzone A/C Cool Refrigerant 1234yf Replacement - 170 g (6 oz.) SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Flash Point (°C), Method - Flashback N Evaporation Rate (n-Butyl Acetate = 1) N VOC Content > Solubility in water

- 104 ° C. (Propane). Closed cup. N/A. No data. > 95 wt.%. Not soluble in water. 450°C (842°F). (Propane). N/A. 2.0. (Propane). 9.5. (Propane). N/A. N/A.

SECTION 10: STABILITY AND REACTIVITY

Reactivity Chemical Stability Possibility of Hazardous Reactions
Conditions to Avoid
Incompatible Materials Hazardous Decomposition Products

Product not reactive under normal conditions of use. Material is stable under normal conditions. Will not occur. Avoid sources of heat and flame, and electrostatic charge. Keep away from heat. Strong oxidizing agents. See Section 05.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	L	_C50	LD50
Propane	6	58 mg/L (Rat - 4 hrs)	Not available
Isobutane	6	58 mg/L (Rat - 4 hrs)	Not available
Information on Likely Routes of Exposure: Routes of entry - Inhalation	Yes. Yes. No. No. Inhalation: Vapors have a nausea. Prolong inhalation Can cause frostbites. N/A. N/A. No information is available None of the ingredients are No information is available Not classified. Not classified.	narcotic effect and may cause hea n may be harmful. a, and no adverse effects are expe e listed as possibly carcinogenic to	adache, fatigue, dizziness and cted. o humans by IARC or ACGIH.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity	May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment.
Persistence and degradability Bioaccumulation Potential Mobility in Soil Other Adverse Effects	The product itself has not been tested. The product itself has not been tested.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods.....

This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.



SAFETY DATA SHEET

Page 4

PRODUCT: emzone A/C Cool Refrigerant 1234yf Replacement - 170 g (6 oz.)

CODE: EM-045830

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)	UN1950, AEROSOLS, Class 2.1, Ltd. Qty.
DOT (US-Road)	UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D.
IMDG (International- Marine)	UN1950, AEROSOLS, Class 2.1, Ltd. Qty.
IATA (International- Air)	UN1950, AEROSOLS, Class 2.1, Ltd. Qtý.

SECTION 15: REGULATORY INFORMATION

Canada Regulations: Canadian Environmental Protection Act (CEPA)	Refer to Section 2 for a WHMIS 2015 Classification for this product. All ingredients listed appear on the Domestic Substances List (DSL).
ÙS Regulations TSCA Inventory Status OSHA	All components are listed on TSCA . This product is considered hazardous under the Federal OSHA hazard communication
California Proposition 65	standard.

SECTION 16: OTHER INFORMATION

Disclaimer	The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.
Abbreviations	ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous
Prepared by Latest Revision	Materials Information System STOT: Specific Target Organ Toxicity. Regulatory Affairs 2021-05-10

